

# PRO 92cW & PRO 92cW-TH

pro series microphones

## Omnidirectional Condenser Wireless Headworn Microphones



### Features

- Designed for lecturers, presenters, houses of worship and other applications requiring clear, articulate vocal reproduction
- Flexible, contoured loop hooks over either ear for a comfortable fit
- Natural, smooth frequency response optimized for vocal reproduction
- Rugged construction designed to meet the challenges of day-to-day use
- Offered in black and beige (-TH) models
- Terminated for use with all Audio-Technica UniPak® wireless systems

### Description

The PRO 92cW is a headworn condenser microphone with an omnidirectional polar pattern. It is designed to provide articulate vocal reproduction for lecturers, presenters and houses of worship.

The microphone includes a 1.4 m (55") permanently attached miniature cable. Its free end terminates in a locking 4-pin connector for use with Audio-Technica UniPak® body-pack transmitters.

The microphone comes equipped with a windscreen, a cable clip and a carrying pouch. The microphone is available in black and beige.

### Operation and Maintenance

The flexible design of the PRO 92cW enables it to be worn on either the left or right ear. Position the lightweight contoured earpiece around your ear, so that the boom extends from the top of your ear. Remove the PRO 92cW and bend a gentle curve in the microphone's boom to follow the contour of your face. Again, hook the earpiece around your ear, adjusting the earpiece and boom as needed to achieve a secure, comfortable fit, so that the microphone is not dislodged by shaking your head.

A cable clip is provided for strain relief, allowing the microphone to remain securely in place without the weight of the cable pulling on the headset. To install the cable clip, slip the cable into the snap-on connector and attach the clip to clothing, leaving enough slack on the microphone side of the clip to allow for free, comfortable motion.

Avoid leaving the microphone in the open sun or in areas where temperatures exceed 110° F (43° C) for extended periods. Extremely high humidity should also be avoided.

To reduce the environmental impact of a multi-language printed document, product information is available online at [www.audio-technica.com](http://www.audio-technica.com) in a selection of languages.

Afin de réduire l'impact sur l'environnement de l'impression de plusieurs langues, les informations concernant les produits sont disponibles sur le site [www.audio-technica.com](http://www.audio-technica.com) dans une large sélection de langue.

Para reducir el impacto al medioambiente, y reducir la producción de documentos en varios leguajes, información de nuestros productos están disponibles en nuestra página del Internet: [www.audio-technica.com](http://www.audio-technica.com).

Para reduzir o impacto ecológico de um documento impresso de várias linguas, a Audio-Technica providência as informações dos seus produtos em diversas linguas na [www.audio-technica.com](http://www.audio-technica.com).

Per evitare l'impatto ambientale che la stampa di questo documento determinerebbe, le informazioni sui prodotti sono disponibili online in diverse lingue sul sito [www.audio-technica.com](http://www.audio-technica.com).

Der Umwelt zuliebe finden Sie die Produktinformationen in deutscher Sprache und weiteren Sprachen auf unserer Homepage: [www.audio-technica.com](http://www.audio-technica.com).

Om de gevolgen van een gedrukte meertalige handleiding op het milieu te verkleinen, is productinformatie in verschillende talen "on-line" beschikbaar op: [www.audio-technica.com](http://www.audio-technica.com).

本公司基於減少對環境的影響，將不作多語言文件的印刷，有關產品訊息可在 [www.audio-technica.com](http://www.audio-technica.com) 的官方網頁上選擇所屬語言及瀏覽。

本公司基于减少对环境的影响，将不作多语言文档的印刷，有关产品信息可在 [www.audio-technica.com](http://www.audio-technica.com) 的官方网页上选择所属语言和浏览。

자원 절약, 환경 보호를 위해 국문 사용 설명서는 인쇄하지 않았습니다. 제품 정보는 [www.audio-technica.com](http://www.audio-technica.com) 에서 원하는 언어 선택 후에 다운로드 받으실 수 있습니다.

### Specifications

Element	Condenser
Polar pattern	Omnidirectional
Frequency response	20-20,000 Hz
Open circuit sensitivity	-45 dB (5.6 mV) re 1V at 1 Pa
Maximum input sound level	116 dB SPL, 1 kHz at 1% T.H.D.
Signal-to-noise ratio <sup>1</sup>	60 dB, 1 kHz at 1 Pa
Current Consumption	0.3 mA typical at 5V
Voltage Range	1.5-9V
Weight	Microphone & boom: 4 g (0.14 oz) Microphone, boom, connector & cable: 24 g (0.84 oz)
Dimensions	Microphone: 21.7 mm (0.85") long, 9.2 mm (0.36") diameter Boom: 110.0 mm (4.33") long, 2.4 mm (0.09") boom diameter
Cable	1.4 m (55") terminated with locking 4-pin connector for use with A-T UniPak® body-pack transmitters
Audio-Technica case style	M38
Accessories furnished	AT8442 cable clip; AT8158 windscreen; Carrying pouch


In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request.

1 Pascal = 10 dynes/cm<sup>2</sup> = 10 microbars = 94 dB SPL

<sup>1</sup> Typical, A-weighted, using Audio Precision System One.


Specifications are subject to change without notice.

frequency response: 20–20,000 Hz




LEGEND — 12" or more on axis  
--- Roll-off

polar pattern



SCALE IS 5 DECIBELS PER DIVISION



cW, cW-TH

Pin	Function
Pin 1	Ground/Shield
Pin 2	Instrument
Pin 3	Mic Audio
Pin 4	Bias + In



Audio-Technica Corporation  
[www.audio-technica.com](http://www.audio-technica.com) ©2015 Audio-Technica

P52035-01